

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 63-099246
(43)Date of publication of application : 30.04.1988

(51)Int.Cl. C08J 9/42
B01D 13/04

(21)Application number : 62-240627 (71)Applicant : JAPAN GORE TEX INC
(22)Date of filing : 28.09.1987 (72)Inventor : KATO HIROSHI
KOMADA ICHIRO
KAZUYASU SATORU

(54) FILMY RAW MATERIAL

(57)Abstract:

PURPOSE: To obtain a functional filmy raw material having excellent mechanical strength and dimensional stability and suitable for the treatment of various liquid and gas, by uniformly attaching and integrating a perfluorinated ion exchange resin to a porous film of polytetrafluoroethylene.

CONSTITUTION: A perfluorinated ion exchange resin is uniformly attached and integrated to a porous film of polytetrafluoroethylene e.g. by impregnating perfluorinated ion exchange resin liquid in a porous film of polytetrafluoroethylene (having a porosity of $\geq 35\%$, especially $\geq 40\%$). The weight ratio of impregnated ion exchange resin to the porous film is 3W90%, especially 10W30%. The whole film can be imparted with hydrophilic property or both hydrophobic and hydrophilic properties by proper selection of the production process.